

Amoladoras de troqueles neumáticas

NOVEDAD

- 0,25-0,30 kW.
 - Carcasa en composite.
 - Contiene: pinza de 6 mm y 1/4".
- Accesorios: **LG1-K284**
(CPN: 80152119), escape remoto.

335SC4A - 35 000 rpm
330SC4A - 30 000 rpm
325SC4A - 25 000 rpm

Sólo 0,4 kg
y 166 mm.



330XC4A - 30 000 rpm
325XC4A - 25 000 rpm

Sólo 0,6 kg.



320AC4A - 20 000 rpm
314AC4A - 14 000 rpm
312AC4A - 12 000 rpm

Sólo 0,55 kg
y 170 mm.



NOVEDAD

5108MAX

- 0,30 kW.
- 25 000 rpm.
- Sólo 0,46 kg y 172 mm.
- Carcasa en composite.
- Contiene: pinza de 6 mm y 1/4".



308B

- 0,25 kW.
- 25 000 rpm.
- Sólo 0,46 kg y 172 mm.
- Contiene: pinza de 6 mm y 1/4".



307B

- 0,19 kW.
- 28 000 rpm.
- Sólo 0,33 kg y 125 mm.
- Contiene: pinza de 6 mm y 1/4".



5102MAX

- 0,30 kW.
- 20 000 rpm.
- Sólo 0,64 kg y 178 mm.
- Carcasa en composite.
- Contiene: pinza de 6 mm y 1/4".



302B

- 0,25 kW.
- 20 000 rpm.
- Sólo 0,58 kg y 175 mm.
- Contiene: pinza de 6 mm y 1/4".



301B

- 0,19 kW.
- 21 000 rpm.
- Sólo 0,46 kg y 128 mm.
- Contiene: pinza de 6 mm y 1/4".



LA429-EU

- 0,42 kW.
- 22 000 rpm.
- Sólo 0,54 kg.
- Contiene: 10 muelas.



Pinzas de recambio



301-700B

Pinzas de recambio (Erickson) para 3...C4A

DG110-700-G2	03641743	Ø 1/8"
DG110-700-6MM	04261053	Ø 6 mm
DG110-700-G4	03641602	Ø 1/4"

Pinzas de recambio para 301B, 302B, 307B, 308B, 5102MAX, 5108MAX y LA429-EU

301-700C	80128952	Ø 1/8"
301-700B	04552600	Ø 6 mm
301-700	80102346	Ø 1/4"

Especificaciones a 6,2 bar

	CPN											
Amoladoras rectas												
335SC4A	45763489	6mm + 1/4"	0,28	35 000	0,40	166	1/4"	10	3,8	14,2	78,4	3,0 / 0,8
330SC4A	45762390	6mm + 1/4"	0,25	30 000	0,40	166	1/4"	10	3,8	14,2	77,2	3,8 / 1,9
330XC4A	45763547	6mm + 1/4"	0,25	30 000	0,62	244	1/4"	10	3,8	14,2	80,2	< 2,5
325SC4A	45752366	6mm + 1/4"	0,30	25 000	0,40	166	1/4"	10	3,8	15,1	78,6	2,6 / 1,1
325XC4A	45763521	6mm + 1/4"	0,30	25 000	0,62	244	1/4"	10	3,8	15,6	78,6	< 2,5
5108MAX	48488340	6mm + 1/4"	0,30	25 000	0,46	172	1/4"	10	2,8	11,8	83,3	1,8 / 0,8
308B	48488332	6mm + 1/4"	0,25	25 000	0,46	172	1/4"	10	3,3	13,2	92,0	3,7 / 1,2
307B	48488316	6mm + 1/4"	0,19	28 000	0,33	125	1/4"	10	2,8	11,3	83,0	4,5 / 1,1
LA429-EU	01328558	3mm + 6mm	0,42	22 000	0,54	142	1/4"	10	1,8	9,4	91,0	3,2 / 1,7
Amoladoras angular												
320AC4A	45763471	6mm + 1/4"	0,30	20 000	0,55	170	1/4"	10	3,8	15,1	78,6	2,5 / 1,1
314AC4A	45763455	6mm + 1/4"	0,25	14 000	0,55	170	1/4"	10	3,8	14,2	80,2	3,2 / 0,7
312AC4A	45754595	6mm + 1/4"	0,30	12 000	0,55	170	1/4"	10	3,8	15,1	78,6	3,4 / 1,0
5102MAX	48488357	6mm + 1/4"	0,30	20 000	0,64	180	1/4"	10	2,8	11,8	84,1	3,3 / 1,1
302B	48488365	6mm + 1/4"	0,25	20 000	0,58	175	1/4"	10	2,8	10,8	90,0	5,5 / 1,5
301B	48488308	6mm + 1/4"	0,19	21 000	0,46	128	1/4"	10	2,8	11,3	91,8	5,9 / 1,0

(1) ISO28927 - medición en tres ejes: nivel de vibración / incertidumbre de medida.

Amoladoras angulares y herramientas de corte



NOVEDAD

345MAX-M

Ø 125 mm

3445MAX-M

Ø 115 mm

- 0,66 kW.
- 12 000 rpm.
- Regulador de velocidad interno.
- Carcasa en composite.
- Escape remoto.

3445MAX-M

LA422-EU - Ø 125 mm













LA421-EU - Ø 100 mm

- 0,50 kW.
- 12 000 rpm.



LA422-EU

Especificaciones a 6,2 bar

	CPN	 mm	 mm	 kW	 rpm	 kg	 mm	 NPTF	 mm	 L/s	 L/s	 dB(A)	 m/s ² / K ⁽¹⁾
345MAX-M	45664257	125	M14	0,66	12 000	1,56	245	1/4"	10	4,9	19,3	79,6	7,9 / 0,7
3445MAX-M	45664240	115	M14	0,66	12 000	1,53	245	1/4"	10	4,9	19,3	79,6	6,4 / 2,0
LA422-EU	01328582	125	3/8"-24	0,50	12 000	1,75	229	1/4"	10	2,8	10,4	85,6	6,0 / 2,1
LA421-EU	01328632	100	3/8"-24	0,50	12 000	1,75	229	1/4"	10	2,8	10,4	85,6	4,8 / 1,4

(1) ISO28927 - medición en tres ejes: nivel de vibración / incertidumbre de medida.

Amoladoras para neumáticos

327LS

- 0,38 kW.
- 3 000 rpm.
- Sólo 0,50 kg.
- Escape remoto.



22 000 rpm














327-EU

- Portabrocas estándar: 10 mm.
- 0,38 kW.
- Sólo 0,73 kg.

Accesorios: **327LS-K284** (CPN: 10323095),
Escape remoto.

Especificaciones a 6,2 bar

	CPN		 kW	 rpm	 kg	 mm	 NPTF	 mm	 L/s	 L/s	 dB(A)	 m/s ² / K(1)
Amoladoras para neumáticos												
327LS	01371699	7/16"□	0,38	3 000	0,50	216	1/4"	10	6,6	12,6	77,4 ⁽²⁾	<2,5
327-EU	01343771	10 mm	0,38	22 000	0,73	224	1/4"	10	7,1	12,6	87,9	4,6 / 1,1

(1) ISO28927 - medición en tres ejes: nivel de vibración / incertidumbre de medida – (2) Escape remoto.